

Agro Waste Kraft Technique Data Sheet

GSM	B.F	RCT(Kg/m)		COBB (gr/m ²)	TEAR FACTOR	DOUBLE FOLD		MOISTURE %
		CD	MD			MD	CD	
120±5%	20	1.05	0.90	45-50	48/58	15	10	7.5±1%
140±5%	20	1.40	1.10	45-50	52/62	15	10	7.5±1%
150±5%	20	1.50	1.20	45-50	0.8	15	10	7.5±1%
180±5%	20	2.00	1.50	45-50	56/66	15	10	7.5±1%
200±5%	20	2.30	1.85	45-50	58/68	15	10	7.5±1%
120±5%	22	1.20	1.00	40-45	50/60	18	12	7.5±1%
150±5%	22	1.70	1.40	40-45	54/64	18	12	7.5±1%
180±5%	22	2.28	1.60	40-45	56/66	18	12	7.5±1%
150±5%	22Color	1.60	1.30	40±5	57/67	24	18	7.5±1%
180±5%	22Color	2.40	1.70	40±5	60/70	24	18	7.5±1%
150±5%	25Color	2.00	1.50	40±5	60/70	28	20	7.5±1%
180±5%	25Color	2.50	1.90	40±5	62/72	28	22	7.5±1%
180±5%	28Color	3.00	2.20	35±5	65/75	50	40	7.5±1%
180±5%	35Color	3.20	2.40	35±5	73/85	85	70	7.5±1%